



AD510-4 Passive Iridium Antenna – Marine or Land

An extremely robust passive antenna designed for use with all the Iridium series of Satellite Phones .

Specifications:

Max. Diameter	87 mm.
Height (including Connector)	100 mm.
Weight (including Bracket)	1 Kg
Operating Temp.	-40 to +85% C.
Connector	N Type female.
VSWR	<2 : 1
Impedance	50 ohms &
Frequency	1610-1630 Mhz.
Polarisation	Right hand circular.



Provides superior performance for external mounting in harsh or marine environments. The radome is 4 mm GRP/Polyester mix whilst the base is milled from aluminium and hard anodised giving an attractive green finish, which is mechanically resilient and resistant to corrosion. The unit is designed for free air mounting and no ground plane is required.

The bracket (AD510-2) provided with each antenna can be attached to vertical or horizontal spars up to 60mm in diameter using the U bolts provided. Connection to the Iridium handset is made with an appropriate coaxial cable via a TNC on the underside of the antenna.

Mounting Bracket:

Heavy Duty Marine Alloy

Vertical or Horizontal pole mount.

Pole mount up to 60 mm.

Supplied complete with stainless U bolts and nuts.



Gardline Communications Inc
1880 South Dairy Ashford Ste#108
Houston, Texas 77077
Phone 281-679-6141
Fax 281-597-8293
www.gardlinecomms.us